

Conwed Fibers® EnviroBlend™ with SlikShot™ Wood/Cellulose Blend

Designed to deliver optimum performance due to the addition of SlikShot, a proven flocculant!

- Conwed Fibers® EnviroBlend™ with SlikShot™ has the added value of enhanced coverage and assists the mulch in adhering to the soil surface
- Combines 100% Thermally Refined® wood fiber with the highest quality cellulose, allowing for up to 15-20% greater coverage vs. competitor's blend products
- EnviroBlend covers more ground than cellulose without a big jump in price
- The blend of wood and cellulose is both easy to mix and spray, combining good yield and erosion control qualities
- Thermally Refined wood fibers hold up to 50% more water than competitor's products, improving turf coverage
- Non-toxic and environmentally safe
- Maximum slope length of 23 feet
- Use approved mechanically agitated equipment for optimum pumping and application performance
- EnviroBlend functional longevity is ≤ 3 months



Product Composition:

Thermally Refined® Wood Fibers (minimum) – 60% \pm 3%
 Cellulose Fiber (maximum) – 27% \pm 3%
 SlikShot™ – 1% \pm 0.5%
 Moisture Content – 12% \pm 3%

(40) 50-lb bales per pallet

| <u>Slope Gradient/Condition</u> | <u>Rate</u> |
|---------------------------------|--------------|
| $\leq 4H:1V$ | 2000 lb/acre |
| $> 4H:1V$ and $\leq 3H:1V$ | 2500 lb/acre |

